

AMENDMENTS TO THE CLAIMS

1 (currently amended) An apparatus for displaying images comprising a TV receiver operable to display at least one image from a recording medium and a remote controller operable to control the TV receiver,

wherein the TV receiver comprises:

a media insertion means for inserting the recording medium;

a media control means for forming a display image list, based on image information from the recording medium, when detecting insertion of the recording medium into the media insertion means;

a first display-image-list storage means for storing the display image list;

a first display means for displaying at least one of ~~the image and image~~ information and one or more images; and

a first control means for transmitting the display image list and ~~images~~the image stored in the recording medium to the remote controller, and for, when receiving control information from the remote controller, outputting at least one of ~~the image and image~~ information and the one or more images from the recording medium to the first display means based on the control information and the display image list stored in the first display-image-list storage means; and

wherein the remote controller comprises:

a second display-image-list storage means for storing the display image list;

a second display means for displaying at least one of ~~the image and image~~ information and the one or more images; and

a second control means for making the second display-image-list storage means store the display image list when receiving the display image list from the TV receiver, for transmitting the control information to the TV receiver when receiving the control information from a user, and for outputting at least one of ~~the image and image~~ information and the one or more images received from the TV receiver to the second display means based on the control information and the display image list stored in the second display-image-list storage means,

wherein the first display means and the second display means are operable to display

images of the one or more images as a two-dimensional array of thumbnail images, in which a first axis of the two-dimensional array represents a time period, and

wherein the first control means and the second control means are operable to prevent the first display means and the second display means, respectively, from displaying a time period when no image from the time period exists in the recording medium.

2 (canceled)

3 (currently amended) The apparatus for displaying images according to claim 12,

wherein a second axis of the two-dimensional array of thumbnail images represents a photography location, the second display means displays the thumbnail image from the recording medium two dimensionally by putting a time period on one of a vertical axis and a horizontal axis, and a photography location on an other axis.

4 (currently amended) A method for displaying images for a TV receiver operable to display at least one image from a recording medium and a remote controller operable to control the TV receiver, said method comprising:

forming, in the TV receiver, a display image list, based on image information from the recording medium, when detecting insertion of the recording medium into the TV receiver;

storing the display image list in the TV receiver;

transmitting the display image list from the TV receiver to the remote controller;

transmitting one or more images~~the image~~ stored in the recording medium to the remote controller;

displaying on the TV receiver at least one of the image and image information and the one or more images stored in the recording medium, when receiving control information from the remote controller, based on the control information and the stored display image list;

storing the display image list received from the TV receiver in the remote controller;

transmitting, when receiving control information from a user, the control information to the TV receiver; and

displaying on the remote controller at least one of the image and image information and

the one or more images received from the TV receiver based on the control information and the display image list stored,

wherein the displaying on the TV receiver and the displaying on the remote controller include displaying the one or more images as a two-dimensional array of thumbnail images, in which a first axis of the two-dimensional array represents a time period, and

wherein the displaying on the TV receiver and the displaying on the remote controller include preventing the displaying on the TV receiver and the displaying on the remote controller, respectively, of a time period when no image from the time period exists in the recording medium.

5 (canceled)

6 (currently amended) The method for displaying images according to claim 45,

wherein a second axis of the two-dimensional array of thumbnail images represents a photography location, the displaying on the remote controller comprises displaying the thumbnail image from the recording medium two-dimensionally by putting a time period on one of a vertical axis and a horizontal axis, and a photography location on an other axis.

7 (previously presented) The method for displaying images according to claim 4, further comprising

deleting the display image list stored in the remote controller when detecting extraction of the recording medium from the TV receiver.

8 (previously presented) The apparatus for displaying images according to claim 1,

wherein the second control means deletes the display image list stored in the second display-image-list storage means when detecting extraction of the recording medium from the media insertion means.